




Stucco IP2013




Canvas IP2009



Adobe IP2008




Oasis IP2011




Arctic IP2012




Zen IP2015




Ore IP2004




Tranquil IP2017



Aqua IP2018



Lunar IP2005



Mineral IP2003



Ebony IP2001

Altro Impressionist™ II



Ease of cleaning and superior colour retention qualities make this product ideal for public circulation areas, school corridors, classrooms, hospital streets, shops and supermarkets.

Standards and accreditation

Meets and exceeds the requirements of BS EN 649 and BS EN 13845.

Slip resistance

Greater than or equal to 36; low risk of slipping (UK Slip Resistance Guidelines); R10, DIN 51130. The construction of Altro safety flooring ensures that its slip resistance is maintained throughout the life of the product.

Specification

Format	Roll	
Dimensions	20m x 2m	(EN426)
Thickness	2.0mm	(EN428)
Weight	2.4kg/m ²	(EN430)

Performance

Indentation	<0.1mm	(EN433)
Dimensional stability	<0.4%	(EN434)
Flexibility	PASS 20mm mandrel	(EN435)
Colourfastness	>6	(EN20105B02: Method 3)
Fire performance	Class 1	(BS476: Part 7 1997)
	Class B _{fl} s1	(EN13501-1)
	28kW/m ²	(EN ISO 9239-1)
	Pass	(EN ISO 11925-2)
Sound absorption	5dB	(ISO 140-8)
Abrasion wear	Group T	(EN660-2)
	Pass	(EN425)
Classification	Homogenous	(EN685)
	Class 34, 43	

Warranties

Warranty 7 years (subject to conditions on warranty form attached to every roll of Altro safety flooring).

Life expectancy 15+ years (under many traffic conditions, wear is comparable to epoxy and quarry tiles).

Chemicals

Tested to DIN 51958, EN 423

Resists Common dilute acids, alkalis and many organic solvents

Caution Ketone solvents.

Chemical spillages should always be removed immediately to protect the floor. For areas liable to chemical spillages, please consult Altro for technical advice.

N.B. More information on performance and standards is available in Altro Flooring and Walling brochures or at www.altro.com

Staining

Certain chemicals may cause staining of vinyl. Traffic stain can be caused by oil residue, certain cleaning agents, asphalt and anti-oxidants in some types of rubber. For further information or advice, please contact Altro.

Colour choice

The colour of Altro safety flooring should be carefully chosen with expected traffic conditions in mind and protective measures such as the use of barrier matting, should be taken wherever possible

versatile collection / safety flooring Altro Impressionist II

our promise to deliver



the highest quality products & services



Resilient Flooring Range of the Year
(6th year running)



Materials of composition

Matrix	High quality vinyl
Inclusions	Aluminium oxide granules throughout. Silicon carbide, quartz and coloured vinyl chips in surface layer
Backing	Non-woven polyester/cellulose with glass fibre reinforcement
Wear layer	2mm

Recommended cleaning methods



no.1 in independent field trials

Machine or hand scrubbing and Altroclean 44™ or other Altro approved cleaners. Technical advances to Altro safety floors significantly improve their cleaning characteristics. Refer to Altro safety flooring routine

maintenance instructions for comprehensive cleaning advice and chemicals at www.altro.com or contact 01462 707600.

N.B. Where maximum slip resistance is not required, AltroGloss™ 211, may be applied. However, it is the building owner's responsibility to first carry out the relevant Health & Safety assessment.



Biological

Excellent surface antibacterial activity due to bacteriostat incorporation*.

*Please consult Altro Technical Services.

Installation and maintenance

All installations in accordance with Code of Practice BS 8203:2001, and Altro safety flooring installation instructions.

Joints	All hot-welded
Subfloor	As Code of Practice, with effective DPM where necessary
Adhesives	As recommended in Altro safety flooring installation instructions, the Altro price list or at www.altro.com

N.B. Failure to install and maintain Altro floors in accordance with 'Altro safety flooring installation instructions' can affect their performance and slip resistance. Floors should be protected from other trades and thoroughly cleaned before handover.

Altro flooring and walling ranges

Products include safety flooring, smooth flooring, resin systems, Mondo rubber, sports flooring, hygienic wall coatings, hygienic PVCu walling and ceiling systems, hygienic doorsets, decorative wall coatings and protective wall coatings. For more information ask for the Altro Flooring and Walling Solutions brochures appropriate to your industry sector, or visit www.altro.com

Sample specification

The slip resistant vinyl sheet flooring to be Altro safety flooring Impressionist II, thickness 2.0mm, width 2000mm, colour (...), as manufactured by Altro. All flooring to be hot welded and laid according to the manufacturer's instructions with recommended adhesives and sealants.

NBS model specification is available for downloading on www.altro.com or telephone 01462 707600.

Prior to specification please ensure you are referring to the most recent sample card.



To obtain individual samples use the SampleExpress service. Please quote the product range and product name/number. Larger samples are also available but may take a few days.

Explore Light. Explore Colour.
Explore Mood, At www.altro.com

explore altroism at www.altro.com

Altro Limited, Works Road, Letchworth Garden City, Hertfordshire SG6 1NW. Tel: 01462 707600 Fax: 01462 707515 e-mail: enquiries@altro.com

Altro, Altro Impressionist, Altroclean, AltroGloss and SampleExpress are trademarks of Altro Limited.