

MANUAL SECTION	ISSUE DATE	AUTHORISED	REPLACES	PAGE
Interior Finishes	March 1996	PM	July 1994	1 of 2

MULTITONE

GENERIC TYPE:

Multitone is a vinyl emulsion coating.

PROPERTIES/FEATURES:

Multitone is a decorative durable multicolour spray coating for interior use.

Duplicates the look of natural materials e.g. cork, leather, granite.

Can be adapted to any decor.

Uniform appearance over a wide variety of substrates.

Single coat covers completely.

Good chemical and stain resistance.

Touch ups blend in well and defy detection.

Excellent washability and scrub resistance.

SUGGESTED USES:

Interior walls and ceilings.

Furniture and fixtures

Office buildings.

Reception areas, shops and sales displays.

Kitchens, laundries, bathrooms.

No warranty either expressed or implied or statutory is made by NUPLEX in this document except as expressly stated in any sale and purchase agreement entered into between NUPLEX and the buyer.

This document is a technical data information sheet. The description of the product or products and the properties of the product or products contained in this document is for the sole purpose of identifying the product or products and describing their property or properties and does not constitute a warranty that the product or its properties shall conform to that description; nor is the description of the product and/or its properties a warranty by NUPLEX that the goods are suitable for a particular purpose.

NUPLEX CONSTRUCTION PRODUCTS

POBox 12841, Penrose, Auckland Telephone 0-9-5792029 Fax 0-9-5253709 www.nuplexbuilding.co.nz email: bpdsales@nuplex.co.nz

H A M I L T O N	PALMERSTON NORTH	W E L L I N G T O N	C H R I S T C H U R C H
Telephone 0-7-847 8658	Telephone 0-6-353 3685	Telephone 0-4-499 1341	Telephone 0-3-366 6802
Fax 0-7-847 3766	Fax 0-6-353 3632	Fax 0-4-471 5709	Fax 0-3-365 7845

MULTITONE (cont'd)**NOT RECOMMENDED:**

Exterior use.

Areas subjected to chemical or physical attack.

Application to substrates subjected to excessive structural movement.

Application below +10°C.

APPLICATION METHOD:

Conventional spray.

COVERAGE RATE:

3-4m²/litre.

The above coverage rates are not definitive and will vary depending on surface texture and desired film build.

THINNING:

Not necessary Multitone is supplied ready to spray.

DRY TIMES:

Touch - 3-4 hours.

Full use 24 hours.

CLEANUP:

Flush equipment with water followed by mineral spirits or lacquer thinners.

SAFETY PRECAUTIONS:

Do not breathe vapours or spray mist.

Use with adequate ventilation.

Avoid skin and eye contact.

Contents are flammable; contains petroleum distillate.

SHELF LIFE:

6 months in unopened containers.

PACKAGING:

4 litre, plastic pails

20 litre, plastic pails

EARLY FIRE HAZARD:

Ignitability	12
--------------	----

Spread of Flame	0
-----------------	---

Heat Evolved	3
--------------	---

Smoke Developed	5
-----------------	---

(Ref APL #9231, 7 September 1992)