


TRUESTIK

Adhesives for bonding floorcoverings



TRUESTIK FLOORING ADHESIVES

Uses:

Truestik adhesives are high quality adhesives used to bond flooring products. They have high tackiness, good bond strength and good tack build-up to aid the contractor in the laying process. Suitable for:

- ◆ Vinyl & vinyl backed products.
- ◆ Carpets and underlays in single and double stick applications
- ◆ Rubber flooring
- ◆ Polyurethane or latex foam underlays
- ◆ Timber

Adhesives:

Truestik VA1 Vinyl
Truestik CA1 Carpet SDS
Truestik CA2 Carpet SS
Truestik EA Epoxy Adhesive
Truestik CTA Carpet Tile adhesive

The Truestik range is formulated to have zero chemical emission to assist both the installer & others in the workplace. Select with the "Nuplex Choice" logo.

*The LOCKED FAST brand implies that adhesives must be of proven long-term bond strength as well as environmentally friendly.
The Truestik range complements the standard Lockfast ranges.*

Application:

The adhesives are generally trowel applied. Critical elements to achieve long term, trouble-free bonding are:

- Apply the correct amount of adhesive per m². Bond strength is more directly related to the quantity of adhesive applied than the adhesive type. If in doubt—use more adhesive.
- Undertake a small trial prior to commencement
- Apply the floorcovering into wet adhesive before it dries. Only wet bonding works
- Always roll the material into the adhesive to achieve intimate contact. Ensure the correct weight of roller is being used.
- Take care in excessively hot or cold conditions which both affect application.

Low environmental impact floorcovering

- Use VOC free adhesives.
- Dispose of waste correctly; recycle
- Minimise waste
- Advise site workers of products being used
- Do not spill washings to drains

Features:

Tough flexible bond. Easy to carry 15lt pail
Shelf life 12months in unopened pails. Storage in cool interior areas.
See panel on the right. Close the pail lid tightly after use.

Apply online for a Nuplex certificate in Low VOC, solvent free adhesives.

Limitations:

Waterbased flooring adhesives have medium heat resistance. Vertical applications in very warm environments may cause problems.
These adhesives will resist the normal dampness in concrete but are not waterproof.



Disclaimer: This adhesive is designed for use with commonly available materials. It is the users responsibility to ensure that this adhesive is suitable for use with the particular product being bonded. We suggest trial areas are applied. Advise Nuplex immediately of any issues relating to the use of the product with specific floorcoverings and do not proceed until satisfied

August 2008

Technical Datasheet

Key Features

- ◆ Low impact flooring adhesive
 - ◆ Strong & early tack development.
 - ◆ Strong & permanent bond.
 - ◆ Guaranteed for all commonly used products
 - ◆ Strong tack .
 - ◆ Zero solvent content
VOC free material
Suitable for use in enclosed workspaces. Use of the adhesive will not effect public or others working in the environment.
- ZV solvent FREE.** (ZV refers to Zero VOC (volatile organic content)).

MULTIPURPOSE adhesive for many applications

TRUESTIK products:

Truestik VA1 Vinyl
Truestik CA1 Carpet SDS
Truestik CA2 Carpet SS
Truestik EA Epoxy Adhesive
Truestik CTA Carpet Tile adhesive

The Truestik range is formulated to have zero chemical emission to assist both the installer & others in the workplace.

Phone: 0508-882288

Email: ncpsales@nuplex.co.nz
www.nuplexconstruction.co.nz

nuplex

Construction Products